



## TECHNICAL DATA / FEATURES

- dimensions: 176x87x86
- luminous flux of the LED module: 5500 lm, 4000 lm, 3000 lm
- luminous flux of the lamp: 4400 lm, 3200 lm, 2400 lm
- maximum power: 70W, 40W, 35W
- nominal voltage: 12V-24V DC
- permissible power supply voltage: 10.5V-30V DC
- source of light: 10 x LED
- colour temperature: 5700-7000K
- light distribution angle: 4°
- IP rating: IP67, IP69K, IP66
- work temperature: -40°C - +80°C
- housing's material: aluminium
- lens' material: plastic
- built-in connectors: AMP Faston 250, Deutsch DT, AMP SuperSeal 1.5
- other: protection:
  - against overheating
  - against reverse polarisation



## ADDITIONAL INFORMATION

Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines and any other places where indicated voltage is available.

The lamps comply with EMC Directive 2004/108/EC. They do not emit electromagnetic interference as well as they are resistant to it's influence.

Correct polarity required.

Mounting: as a freestanding on body panels. They can be installed in an upright or upside down position.

The bracket parts are made of Inox steel.

It is possible to install needed connectors for a version with cable (on request).




Useful parts while installing:

- deutsch plug DT06-2S 2-pin - cat. No. A.07135
- AMP SuperSeal 1,5 plug 2-pin - cat. No. A.07137
- AMP Faston 250 plug 2-pin - cat. No. A.07138

Replacement parts:

- grip - cat. No. AR.54324
- neodymium magnet  $\phi 89/500N$  (1 pc.) - cat. No. CAR4.51320

## DIMENSIONS



Cat. number	Luminous flux			IP rating	IP66	IP67	IP69K	Accessories				Bracket	M8	neodymium magn.	omega grip	Connectors					
	5500 lm	4000 lm	3000 lm					cable 0,15 m	cable 0,5 m	cable 0,8 m	cigarette lighter plug					switch	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	HB3	Delphi 12129615
<b>CRV1P.56801</b>	✓																				
CRV1P.56803	✓																				
CRV1P.56804	✓																				
CRV1P.56887	✓																				
<b>CRV1N.53601</b>		✓																			
CRV1N.53606		✓																			
<b>CRV1N.53604</b>		✓																			
CRV1N.53602		✓																			
<b>CRV1N.53603</b>		✓																			

Cat. number	Luminous flux			IP rating	IP66	IP67	IP69K	Accessories				Bracket	M8	neodymium magn.	omega grip	Connectors					
	5500 lm	4000 lm	3000 lm					cable 0,15 m	cable 0,5 m	cable 0,8 m	cigarette lighter plug					switch	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	HB3	Delphi 12129615
CRV1N.53650		✓																			
<b>CRV1M.53501</b>			✓																		
<b>CRV1M.53506</b>			✓																		
<b>CRV1M.53514</b>			✓																		
<b>CRV1M.53513</b>			✓																		
<b>CRV1M.53521</b>			✓																		
CRV1M.53526			✓																		
CRV1M.53534			✓																		
CRV1M.53533			✓																		