



TECHNICAL DATA / FEATURES

- dimensions: $\phi 117 \times 74$
- luminous flux of the LED module: 3000 lm, 2500 lm, 2000 lm, 1500 lm
- luminous flux of the lamp: 2400 lm, 2000 lm, 1600 lm, 1200 lm
- maximum power: 30W, 29W, 25W, 24W
- nominal voltage: 12V-24V DC
- permissible power supply voltage: 10.5V-30V DC
- source of light: 6 x LED
- colour temperature: 5000-7000K
- light distribution angle: 4°
- IP rating: IP67, IP69K
- work temperature: -40°C - +80°C
- housing's material: aluminium/plastic
- lens' material: plastic
- built-in connectors: Deutsch DT, AMP Faston 250
- other: protection:
 - against overheating
 - against reverse polarisation
- bracket made of Inox steel



ADDITIONAL INFORMATION

Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines and any other places where indicated voltage is available.

The lamps comply with EMC Directive 2004/108/EC. They do not emit electromagnetic interference as well as they are resistant to it's influence.

Correct polarity required.

Equipped with removable protective grille.

It is possible to install needed connectors for a version with cable (on request).

Replacement parts:

neodymium magnet $\phi 89/500N$ (1 pc.) - cat. No. CAR4.51320

brackets - cat. No. CAR1.47300

brackets - cat. No. CAR3.50600



grip - cat. No. AR.54324

Useful parts while installing:

AMP Faston 250 plug 2-pin - cat. No. A.07138

deutsch plug DT06-2S 2-pin - cat. No. A.07135

DIMENSIONS



Cat. number	Luminous flux				IP rating	IP67	IP69K	Accessories	LED module 12V-24V/ handle	cable 0.5 m	cable 4 m	cable 8 m	switch	cigarette lighter plug	Mounting method	any	installed vertically up	rear	Bracket	neodymium magn.	CAR1	CAR3	grip	M8	Connectors	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	Cap / Pin	
	3000 lm	2500 lm	2000 lm	1500 lm																										
CRC3J.57096	✓				✓	✓		✓	✓					✓	✓															
CRC3J.57090	✓				✓	✓		✓	✓					✓	✓															
CRC3F.50495		✓			✓	✓		✓	✓					✓	✓								✓							
CRC3F.50496		✓			✓	✓		✓	✓					✓	✓															
CRC3F.50497		✓			✓	✓		✓	✓					✓	✓											✓			2	
CRC3F.50441		✓			✓	✓		✓	✓					✓	✓										✓			2		
CRC3F.50440		✓			✓	✓		✓	✓					✓	✓										✓			2		
CRC3F.50489		✓			✓	✓		✓	✓	✓				✓	✓															
CRC3F.50425		✓			✓	✓		✓	✓	✓				✓	✓															
CRC3F.50429		✓			✓	✓		✓	✓					✓	✓										✓			2		
CRC3D.50294			✓		✓	✓		✓	✓					✓	✓															
CRC3D.50295			✓		✓	✓		✓	✓					✓	✓															
CRC3D.50225			✓		✓	✓		✓	✓	✓				✓	✓															
CRC3B.49294				✓	✓	✓		✓	✓					✓	✓															
CRC3B.49295				✓	✓	✓		✓	✓					✓	✓															
CRC3B.49239				✓	✓	✓		✓	✓					✓	✓										✓			2		
CRC3B.49238				✓	✓	✓		✓	✓					✓	✓										✓			2		
CRC3B.49225				✓	✓	✓		✓	✓	✓				✓	✓															